

PRODUCT DATA SHEET

TRIDENT PREMIUM RIPSTOP™

01st August 2012

WIDTH	205cm
WEIGHT	690gsm
BASE CLOTH	Polyester 1100 Decitex
WEAVE	9 x 9 per cm / Ripstop 1 x 1 per cm
COATING	PVC paste coated
SURFACE FINISH	High Gloss ROWACRYL protective finish
TEAR STRENGTH Warp/Weft	700 / 600 N
TENSILE STRENGTH Warp/Weft	2800 / 2300 N
U/V STABILITY	3 year minimum
FIRE RETARDANT	N/A
ADHESION	90 N per 5cm
FLEXING	400,000 cycles minimum
FABRICATION METHODS	Hot Wedge, Hot Air or High Frequency Welding: Sewing: Adhesive
FABRIC CARE	OFPANZ Care Label OF-1

NORTH ISLAND: PO Box 97-149, 5 Druces Rd, Manukau City, Auckland, New Zealand
Phone (09) 262 2771, Fax (09) 262 3730 Email: sales@wwiggins.co.nz

SOUTH ISLAND: PO Box 483, 97 Magdala Place, Middleton, Christchurch, New Zealand
Phone (03) 339 4375, Fax (03) 339 7376, Email: chsales@wwiggins.co.nz

IFAI proud member
INDUSTRIAL FABRICS ASSOCIATION INTERNATIONAL
www.ifai.com

IFAI OFPANZ